# STATE OF THE STATE

### आरोग्य विभाग

123

## जिल्हा आरोग्य अधिकारी कार्यालय,जिल्हा परिषद,धाराशिव



दुरध्वनी क्रमांक- ०२४७२-२२०४५१

आरोग्य सेवा

ई-मेल आयडी – dhomedistoreosbad@gmail.com

पिन क्रमांक ४१३५०१

जा.क्र.जिपधा/आवि/औभा/कावि/औषधीभांडार/3074

दि. 28 112 1२०२३

प्रति	,
	9
	<b>२</b>
	<b>ξ</b>
	۶
	५. नोटीस बोर्ड

### विषय - आरोग्यवर्धीनी केंद्रासाठी आवश्यक साहीत्य खरेदी करणे बाबत..

उपरोक्त विषयानुसार आरोग्य विभाग,जिल्हा परिषद,धाराशिव अंतर्गत ४ आरोग्यवर्धीनी केंद्रामध्ये सोबतच्या यादीतील आवश्यक साहीत्य/उपकरणे खरेदी करावयाचे आहे तरी आपल्या फर्मचे प्रती नगाचे सर्व करांसहीत दरपञक देण्यात यावे.

तरी सदर दरपञक दिनांक -28/12/12, २०२३ ते 10/1/12 /२०२३ या कालावधीत कार्यालयीन वेळेत दुपारी ५.०० वाजे पर्यत सिल बंद पाकीटात खालील अटी व शर्तीच्या अधिन राहुन सादर करण्यात यावेत.

### अटी व शर्ती -

- 9.दरपञकातील दर हे सर्व करांसहित या कार्यालयाच्या औषधी भांडारात पोहोच करण्या पर्यतचे असावेत.
- २.वरील साहीत्याचा पुरवठा केल्या नंतर देयक दोन प्रतीत या कार्यालयास सादर करण्यात यावे.
- ३.मागविण्यात आलेले दर पञक रदद करणे किंवा मंजुर करण्याचे अधिकार या कार्यालयाने राखुन ठेवलेले आहेत.
- ४.वरील प्रमाणे अटी व शर्ती मान्य असलेल्या फर्मनेच दर पजके सादर करावीत. तसेच सदर खरेदी ही तातडीची असल्यामुळे पुरवठा तात्काळ करणे आवश्यक असेल.
- ५.साहीत्याचा पुरवठा १५ दिवसात या कार्यालयास करणे बंधनकारक असेल अन्यथा ०.५ % प्रती आठवडा दंड पुरवठा आदेशातील पुर्ण रक्कमेतुन वसुल केला जाईल याची नोंद घ्यावी.
- ६. दरपञक भरताना एका लिफाफयात दोन लिफाफे देण्यात यावेत लिफाफा क्र १ हा तांञीक कागदपञासाठी आहे व साहीत्य/उपकरणाचे दर भरताना एका नगाचे सर्व करांसहीत दर लिफाफा क्र २ मध्ये भरावेत. व तसे लिफाफयावर तांञीक लिफाफा व दराचा लिफाफा असे नाव तसेच फर्मचे नांव नमुद करणे आवश्यक आहे, लिफाफे हे सिलबंद सादर करणे आवश्यक आहे.
- ७. उपकरणे/साहीत्य सोबत दिलेल्या स्पेसिफिकेशन प्रमाणे नसल्याचे आढळून आल्यास सदर उपकरणे/साहीत्य ताब्यात घेण्यात येणार नाही याची नोंद घेण्यात यावी.

# तांञीक लिफाफा क्र १ मध्ये दयावयाच्या बंधनकारक कागदपञाची माहीती

- मुंबई दुकान व संस्था अधिनियम १९४८ अंतर्गत दुकान निरिक्षक यांचे प्रमाणपञ ज्यात
   धंदयाचे स्वरुप नोंदणी आहे असे वैध प्रमाणपञ, उत्पादक असल्यास उत्पादक असल्याचे वैध प्रमाणपञ.
- २. जि.एस.टी. नोंदणी प्रमाणपञ.
- ३. जि.एस.टी.कायदया प्रमाणे माहे जुन २०२३ पर्यन्त भरण्यात आलेल्या रिटर्नची प्रत.
- ४. पॅन कार्ड छायाप्रञ
- ५. मागील तीन वर्षाच्या उलाढालीचे (Balance Sheet) रजिष्टर्ड चार्टर्ड अकाऊटंन्ट यांचे प्रमाणीत प्रमाणपञ सन २०२०-२१,सन २०२१-२२ व सन २०२२-२०२३ या वर्षाचे (प्रती वर्ष किमान रु.१६.०० लक्ष टर्न ओव्हर असणे आवश्यक आहे.) सोबतच्या नमुन्यात
- ६. मागील तीन वर्षाचे नफा व तोटयाचे (Profit & Loss Account Sheet) रजिष्टर्ड चार्टर्ड अकाऊटंन्ट यांचे प्रमाणीत प्रमाणपञ सन २०२०-२१,सन २०२१-२२ व सन २०२२-२०२३ या वर्षाचे.
- पुरवठाधारकांचे नांव शासनाच्या शासिकय किंवा निमशासिकय संस्थे मध्ये काळया यादीत नसल्याचे रु.५००/-च्या मुद्रांकित शुक्लावर (स्टॅप पेपर) प्रतिज्ञापञ देणे बंधनकारक राहील.
- ८. शासन निर्णय उदयोग,उर्जा व कामगार विभाग,मंञालय,मुंबई दिनांक १.१२.२०१६ नुसार हित संबंध नसल्याचे प्रमाणपञ सोबतच्या नमुन्या नुसार देणे बंधनकारक असेल.
- ९. सदर उपकरणे/साहीत्याचा पुरवठा शासिकय/निमशासिकय संस्थेमध्ये केल्याचे किमान प्रती वर्ष एक पुरवठा आदेशाची प्रत (सन २०२०-२१,सन २०२१-२२ व सन २०२२-२०२३)

### दराचा लिफाफा क्र २ मध्ये साहीत्य/उपकरणाचे दर सर्व करांसहीत खालील नमुन्यात भरण्यात यावेत

		5 . 0
अ.क्र	उपकरणे/साहीत्याचे नांव	सर्व करांसहीत एका नगाचे दर
1	Swedana/Sudation Chamber	
2	Nadi Sweda Yantra ( 7 lirs Stainless Steel Cooker)	
3	Nadi Sweda Yantra ( 10 lirs Stainless Steel Cooker)	
4	Infrared lamp for joint swedan	
5	Basti yantra ( Niruha Basti )	
6	Basti yantra ( Anuvasan Basti )	
7	Shirodhara Yantra	
8	Shirobasti	
9	Nasya karma set	
10	Yoga Jal neti pot Plastic 200 ml	
11	Yoga neti pot Stainless Steel 500ml	
12	Yoga Mats	
13	Weighing Machines Adult Digital	
14	Weighing Machines Pediatric	

15	Swab holder	
16	Wheel chair	
17	Wooden chair	
18	Examination stool	
19	Stracher on Trolly	
20	Wheel chair for disabled patient	
21	Computer table	
22	Wooden Snehan Table	And the same of th
23	Hight meter	

( डॉ.सिनिश हरिदास ) जिल्हा आरोग्य अधिकारी जिल्हा परिषद,धाराशिव

Jama /Quidation C	ame Of Items	Specification
Swedana /Sudation Chamber		स्वेदन टेबल/द्रोणी
		७.५ X २.५ X ३ फूट असावे
		वरुन झाकण असावे.
		झाकण हलके असावे.
		शिरोभागी अधार असावा
Nadi Sweda Yantra, '	7 ltrs Stainless Steel	प्रेशर कुकर ७ लिटर
Nadi Sweda Yantra,	10 ltrs Stainless Steel	प्रेशर कुकर १० लिटर
Infra Red Lamp	For Joint Swedan	
Product Specification	on	
Usage/Application	Hospital	NAME OF THE PROPERTY OF THE PR
Light Source Type	LED	
Brand	Vision	
Material	MS	
Positioning	Floor Standing	
lamp from us from	ious quality parameters, clients can avail this us in various power capacities a range, this is moveable and adjustable	
High low Inten	nsity switch Direction, Adjustment can be done	
High low Inten	Direction, Adjustment can be done	स्टेन लेस स्टीलचे किमान १ लिटर द्रावण मावेल असे असावे.
<ul><li>High low Inten</li><li>Height, Angle,</li></ul>	Direction, Adjustment can be done a Basti)	स्टेन लेस स्टीलचे किमान १ लिटर द्रावण मावेल असे असावे. स्टेन लेस स्टीलचे किमान २५० ते ३०० मिली द्रावण मावेल असे असावे.
<ul> <li>High low Inten</li> <li>Height, Angle,</li> </ul> Basti Yantra (Niruh)	Direction, Adjustment can be done a Basti) asan Basti)	स्टेन लेस स्टीलचे किमान १ लिटर द्रावण मावेल असे असावे. स्टेन लेस स्टीलचे किमान २५० ते ३०० मिली द्रावण मावेल असे
<ul> <li>High low Inten</li> <li>Height, Angle,</li> </ul> Basti Yantra (Niruh Basti Yantra (Anuv.)	Direction, Adjustment can be done a Basti) asan Basti)	स्टेन लेस स्टीलचे किमान १ लिटर द्रावण मावेल असे असावे. स्टेन लेस स्टीलचे किमान २५० ते ३०० मिली द्रावण मावेल असे असावे.
<ul> <li>High low Inten</li> <li>Height, Angle,</li> <li>Basti Yantra (Niruh</li> <li>Basti Yantra (Anuv</li> <li>Shirodhara Yantra</li> <li>Shirobasti</li> </ul>	Direction, Adjustment can be done a Basti) asan Basti)	स्टेन लेस स्टीलचे किमान १ लिटर द्रावण मावेल असे असावे. स्टेन लेस स्टीलचे किमान २५० ते ३०० मिली द्रावण मावेल असे असावे. तांब्र धातुचे असावे,किमान २ लिटर द्रावण मावेल असे असावे. २.५ X १२

### आरोग्यवर्धीनी केंद्रासाठी आवश्यक उपकरणे व साहीत्य खरेदीचे स्पेसिफिकेशन

N	ame Of Items	Specification
Swedana /Sudation (	Chamber	स्वेदन टेबल/द्रोणी
Swedana / Sudation Chamber		७.५ x २.५ x ३ फुट असावे
		वरुन झाकण असावे,
		झाकण हलके असावे,
		शिरोभागी अधार असावा
Nadi Sweda Yantra, 7 ltrs Stainless Steel		प्रेशर कुकर ७ लिटर
Nadi Sweda Yantra,	10 ltrs Stainless Steel	प्रेशर कुकर १० लिटर
Infra Red Lamp	For Joint Swedan	
Product Specification		
Usage/Application	Hospital	
Light Source Type	LED	Co.
Brand	Vision	
Material	MS	
Positioning	Floor Standing	
C		
Product Description	,	
	he foremost manufacturer and supplier of	
	Lamp that is used for to transmitting	1000
	body. This lamp is manufactured using	A. C. Sandarian Company of the Compa
	ts with the help of advanced technology. It	
	medical applications in hospitals all across ous quality parameters, clients can avail this	
	us in various power capacities at	
	nge. this is moveable and adjustable.	
Features:		
<ul> <li>High low Intens</li> </ul>	ity switch	
<ul> <li>Height, Angle, I</li> </ul>	Direction, Adjustment can be done	
Basti Yantra (Niruha	Basti)	स्टेन लेस स्टीलचे किमान १ लिटर द्रावण मावेल असे असावे.
Basti Yantra (Anuva	san Basti)	स्टेन लेस स्टीलचे किमान २५० ते ३०० मिली द्रावण मावेल असे
-	··	असावे.
Shirodhara Yantra		तांब्र धातुचे असावे,िकमान २ लिटर द्रावण मावेल असे असावे.
Shirobasti		2.4 X 93
		चामडी पटटा असावा
Nasya Karma Set- N	Made up of Brass	
-	•	- IFON
		415
**		
	White Durable Plastic	
Material) 200 ml	•	and the same of th

oga Jal Neti Pot (Stainless Steel Material) 500 ml	
Yoga Mats	
Colour Multicolor  Brand Generic  Material Ethylene Vinyl Acetate	A September 1997
Weighing Machine –Adult  Personal Baby Weighing Scale for Manual Weight Upto 150 Kgs	
Weighing Machine — Pediatric  Personal Baby Weighing Scale for Manual Weight Upto 10 Kgs with Tray (Cream)	
Swab Holder	Made up of stainless Steel
Wheel Chair  Specification  Florence Metal Base Mid Back Mesh Revolving Office Chair (4 Color Options) (Black).	
Wooden Chair  Specification Size (LxBxH): 20 x 18 x 36 Inch Material: Teak wood	
Examination Stool	As Per Attached Specification
Stracher	As Per Attached Specification
Wheel Chair For Disable Patient	As Per Attached Specification
Computer Table  Description  stainless steel computer desk with solid top and rear rail is a perfect work and storage surface for any Office whereby a strong, easy-clean material is necessary.  Finished in brushed dull polish, the stainless steel rear rail desk comes with 304-grade stainless steel build and a 200kg payload, with a 40mm box section frame. The stainless steel adjustable feet with non-marking rubber base lend stability and strength to the unit.  With a ledge for a regular size computer tower and a keyboard shelf, also manufactured from 304 grade stainless steel, this desk is designed to house your computer safely.  Dimensions (W x D x H unless stated)  Widths available: 1200, 1500 and 1800mm  Depths: 600 and 750mm  Floor clearance: 150mm  Height: 840mm	

	pecifications	
	Computer desk with top and tower shelf - siliconed seal	
1	• Fully welded 304 grade stainless steel	
	Brushed dull polish finish	
	Keyboard/mouse drawer	
	Stainless steel adjustable feet with non-marking rubber base	
	Mobile versions available	
ŀ	Wooden Snehan Table	
	Wooden Shehan Table	७.५ X २.५ X २.५ फुट (मुठ व्यतिरिक्त)
	•	८.९ X २.५ X २.५ फुट (मुठ सहीत)
		टेबल सागवानी असावे
	Hight Meter	
	8	MEGHT
		**************************************
		des.
L		

4.

· is

.

. . .

••

# **Technical Specification of Stretcher Trolley**

1	Overall Size :-	2100mm (L) X 560mm(W) X 820mm(H) Height from Ground
		level to top.
2	Frame of the Trolley :	<ul> <li>a) Trolley frame work, S.S tubular deep fully argon welded with vertical upright 31.75mm OD, 18SWG tubes. Tube should be reinforced at the bottom with 35mm OD, 18SWG tube for fitting the wheels.</li> <li>b) All horizontal stay shall be of 25.4mm OD, 18SWG.</li> <li>c) Supported with non-rusted 200mm x 50mm OD, noiseless smooth moving PU Wheels (04No) with double bearing &amp; double lock arrangement to each wheel.</li> </ul>
3	Removable Stretcher Top :	<ul> <li>a) Stretcher should be removable from trolley.</li> <li>b) Top - S.S. 18SWG Sheet, dished horizontally in middle.</li> <li>c) Stretcher dished sheet should be fitted on 25mm OD,16SWG SS. Tube.</li> <li>d) Three Additional 31.7 x 6 mm S.S. stiffeners should be fully argon welded to main frame, to support S.S. dished top from underneath widthwise.</li> <li>e) Four legs - S.S. 25mm OD,16SWG SS. tube having190mm height fitted rubber bush.</li> <li>f) Push Handle at both ends 25mm OD,16SWG SS. Tube &amp;</li> </ul>
4		covered with PVC Sleeves.  Govt. of Maharashtra Public Health Dept. & Mfg date" must be embossed at visible sight of frame & removable stretcher, must be easily readable
5	Finish:	<ul> <li>a) All S.S. should be deep fully argon seamless welded and polished finished.</li> <li>b) Tow section tops should be smooth edges and burr free and corners should be round off so that there should be no sharp corners.</li> </ul>
6	General Requirements:	<ul> <li>a) All stainless steel sheet &amp; stainless steel tubes/pipes used in manufacturing shall be of 304 S2 grade confirming to IS 6911 of 1992 or latest.</li> <li>b) All dimensions will be considered — Length, Width, Height in millimeter(mm), thickness in gauge (SWG — Standard Wide Gauge), Diameter should consider as Outer Diameter (OD).</li> <li>c) The stretcher trolley must be sturdy, vibration free and self balance.</li> <li>d) The stretcher trolley shall be properly constructed with all welded joints grounded, cleaned and well-formed. Unless otherwise specified, the vertical members shall be perpendiculars to the wheel base and parallel to each other and the horizontal members shall be at right angles to the vertical members.</li> <li>e) The stretcher trolley shall stand on all the legs at the same time on a level surface. All the surfaces shall be smooth and</li> </ul>

free from pitting. Welding shall fully penetrate and shall be sound in every detail and it shall be finished flush. In the finished stage, there shall be no exposed sharp edges in the frame-work or other unsealed formations which may harbor dirt or foreign matter.

- f) The sketch shown in the specification is only indicative for the bidder.
- g) should attached inbuilt small cyliner trolley

h) Tender committee has reserved rights to change dimensions & sketch at any stage of tender.

acuriumono acuriumono Prolitoguela Than CivilHosp 13/0/19.

Amul Wadekaz Biomedical Engly, RRSH, Amravadi

# **Technical Specification of Wheel Chair**

1	Overall Length :-	1060 mm Width : 600mm Height 040
2	Seat Height from floor at the	1050 mm Width : 680mm. Height : 910mm 500mm.
	front:	
3	Seat Height from floor at the back:	450mm
4	Arm Height from seat :	225mm.
5	Seat :	Length: 430mm Width between armrest pipes: 430mm
6	Back- Height :	380mm, Width at seat level : 430mm. Width at the Top: 430mm.
7	Clearance of footrest to floor:	90 to 200mm
8	Back Clearance of frame to floor:	100mm
9	Mean Rim Diameter:	500mm
10	Front Ringing:	Foldable cast aluminum foot res& 200mm OD Strong
		swiveling PU wheels, double bearing, provided in front
11		single position 12mm
12	Rare Wheel :	solid rubber tyre wheels-02 Nos, for self propulsion to hoops of 15.8mm OD, 18SWG tube, mounted on rims, with brake facility.
13		25.4mm OD, 18SWG round tube, S.S.
14		18SWG, S.S.
15		All section tops should be smooth edges and burr free and corners should be round off so that there should be no sharp corners
16	General Requirements:	a) All stainless steel sheet & stainless steel tubes/pipes used in manufacturing shall be of 304 S2 grade confirming to IS 6911 of 1992 or latest. b) All dimensions will be considered — Depth, Width, Height in millimeter(mm), thickness in gauge (SWG — Standard Wide Gauge), Diameter should consider as Outer Diameter (OD). c) The wheel chair must be sturdy, vibration free and self balance. d) The wheel chair shall be properly constructed with all welded joints grounded, cleaned and well-formed. Unless otherwise specified, the vertical members shall be perpendiculars to the wheel base and parallel to each other and the horizontal members shall be at right angles to the vertical members. e) The wheel chair shall stand on all the wheels at the same time on a level surface. Welding shall fully penetrate and shall be sound in every detail and it shall be finished flush. In the finished stage, there shall be no exposed sharp edges in the frame-work or other unsealed formations which may harbor dirt or foreign

by vinny of public of a mi, muchin

18/06/32). Amol Waddeas 6/19. Amol Waddeas 6/19. Blomedical Engineer 13/6/19 13/6/19 matter.

- f) The sketch shown in the specification is only indicative for the bidder.
- g) Tender committee has reserved rights to change dimensions & sketch at any stage of tender.
- h) "Govt. of Maharashtra Public Health Dept. & Mfg date" embossed plate must be riveted at visible sight, Embossed font can easily readable.

MNL Roquell.
There avilloss
13/6/9.

Dr. Vivaya Andre

And Wedley

Bromedon Er's

RRSH Amaras

### Annexure-X

# **Technical Specifications for Patient Stool/Attendant Stool**

Sr. No.	Technical Specifications.	
Ι.	Overall Size:	305mm (L) X 305mm (W) X 545mm (H) Height from Ground level to top.
2.	Top & frame	a) Top S.S. Sheet 18SWG, double bend at each side, mounted on frame structure.
		b) Frame – S.S. tubular 25mm x 25mm, 18SWG
		c) All legs must provide neoprene rubber shoes.
		d) "Govt. of Maharashtra Public Health Dept. & Mfg date" must be embossed at visible sight, must easily readable.
3.	Finish	a) All S.S. should be deep fully argon seamless welded and polished finished.
		b) The section tops should be smooth edges and burr free and corners should be round off so that there should be no sharp corners.
4.	General Requirements:	a) All stainless steel sheet & stainless steel tubes/pipes used in manufacturing shall be of 304 SS grade confirming to IS 6911 of 1992 or latest.
		<ul> <li>b) All dimensions will be considered - Length, Width, Height in millimeter (mm). thickness in gauge (SWG - Standard Wide Gauge), Diameter should consider as Outer Diameter (OD).</li> </ul>
		c) The Patient stool / Attendant stool must be sturdy, vibration free and self-balance.
		d) The Patient stool / Attendant stool shall be properly constructed with all welded joints grounded, cleaned and well-formed. Unless otherwise specified, the vertical members shall be perpendiculars to the wheel base and parallel to each other and the horizontal members shall be at right angles to the vertical members.
		e) The Patient stool / Attendant stool shall stand on all the legs at the same time on a level surface. All the surfaces shall be smooth and free from pitting. Welding shall fully penetrate and shall be sound in every detail and it shall be finished flush. In the finished stage, there shall be no exposed sharp edges in the frame-work or other unsealed formations which may harbor dirt or foreign matter.
		f) Tender committee has reserved rights to change dimensions & sketch at
5.		It should be ISI Mark and Metal Quality-Testing from Govt. Engineering. Colleges/Polytechnic/Reputed Institute.